

INSTALLATION INSTRUCTIONS
TAILLIGHT GUARD
07-ON GMC SIERRA 1500/2500
PART #

PARTS LIST:

1	Driver/Left Taillight Guard	2	4 -.70mm x 15mm Phillips Screws
1	Passenger/Right Taillight Guard	2	4mm Lock Washers
		2	4mm Flat Washers

PROCEDURE:

1. REMOVE CONTENTS FROM BOX. VERIFY ALL PARTS ARE PRESENT. READ INSTRUCTIONS CAREFULLY BEFORE STARTING INSTALLATION.
2. **IMPORTANT!** Cover the finish edge around the taillight housing with masking tape to protect the finish of the vehicle when removing the taillight housing and installing the Taillight Guard.
3. Open the rear door and remove the passenger side screws holding the taillight housing (Figure 1).
4. Grasp the taillight housing with one hand and pull with your other hand gently. **NOTE:** Be sure to pull straight out towards the rear of the vehicle to avoid possible damage. This is the same procedure required to change a burn out taillight bulb in the assembly. For more info see owner's manual on replacing burn taillight bulbs.
5. Position Support Bracket over taillight locating stud (Figure 2), and then snap taillight back onto the vehicle (Figure 3). **NOTE:** Make sure the Support Bracket sticks out straight from the taillight cavity.
6. Position Taillight Guard over taillight and attach it to vehicle using the factory hardware (Figure 4).
7. Attach the Taillight Guard to Support Bracket using the included (1) 4mm x 15mm Phillips Screws, (1) 4mm Lock Washer, and (1) 4mm Flat Washer (Figure 5).
8. Adjust Taillight Guard properly, and then tighten all hardware at this time.
9. Repeat steps 2 – 8 for driver side Taillight Guard.
10. Do periodic inspections to the installation to make sure that all hardware is secure and tight.

To protect your investment, wax this product after installing. Regular waxing is recommended to add a protective layer over the finish. Do not use any type of polish or wax that may contain abrasives that could damage the finish.

For stainless steel: Aluminum polish may be used to polish small scratches and scuffs on the finish. Mild soap may be used also to clean the Taillight Guard.

For gloss black finishes: Mild soap may be used to clean the Taillight Guard.




Fig 1




Fig 2



Fig 3




Fig 4



Fig 5



Fig 6